

Technical sheet

Ref. 010043

Adjustable guardrail for 25 cm wall penetration 1,5m high



The guardrails are fixed on the side or at the bottom of the roof and carry the safety accessories (handrails, baseboards, nets) to provide full protection.

FEATURES

Can be placed directly from the roof with personal protective equipment
 Low investment cost
 Short assembly time
 Low administrative formalities
 Not bulky
 Best Seller
 Scalable with additional parts

SPECIFICATIONS

Length (mm)	1500
Width (mm)	400
Height (mm)	2000
Weight (kg)	0

Technical description

Temporary edge peripheral collective protection spaced at 3m max

New site and renovation with a slope of 10° maximum Adjusted at gutter

eaves adjustment

Anchor point: by screw, U iron and nut

Placed on wall

Roof overhang 0 to 70 cm

Comprises:

- 1 post 1,50 m high (ref. 20227)
- 1 40 cm wall penetration 70 cm overhang (ref 20241 - composed of 1 articulated wall penetration - ref. 20246, 1 nut - ref 30015 and 1 U iron - ref 20622)
- 1 spacer bar 1 m steel (ref. 20014)
- 1 high security pin + beta n°2 - ref. 20020

Actions : To work safely

Trades : Slate / Framework / Metal / Tile