

Technical sheet

Ref. 010125

Guardrail with clamp for purlin 25cm overhang at 1,5m



The guardrails are fixed on the side or at the bottom of the roof and carry the safety accessories (handrails, baseboards, nets) to provide full protection.

FEATURES

Can be placed directly from the roof with personal protective equipment
 Light weight that reduces musculoskeletal disorders
 Low investment cost
 Short assembly time
 Low administrative formalities
 Not bulky
 Best Seller
 Scalable with additional parts

SPECIFICATIONS

Lenght (mm)	1540
Width (mm)	400
Height (mm)	2000
Weight (kg)	0

Technical description

Temporary gutter and side peripheral collective protection spaced at 3m max

New site and renovation with a slope of 30° maximum

Adjustment on gutter

Overhang adjustment up to 1,10

Anchor point: With clamp

Placement on rafter and all types of frame

Full pack: 3ml / 9ml / 12ml

Comprises:

- 1 post 1,50 m high (ref. 20227)
- 1 Steel handrail (ref. 20013)
- 1 clamp for purlin or rafter (ref. 20094)
- 1 High-security pin with cable (ref. 20025)
- 1 high security pin + beta n°2 - ref. 20020
- 1 spacer bar 1,5 m steel (ref. 20114)

Actions : To work safely

Trades : Slate / Framework / Metal / Tile